

DT Series: Connectors

- Current capability: 13 amps
- Thermoplastic housings & wedge locks, rated at -67°F to 257°F
- Silicone elastomer seals create an environmentally sealed connection
- Terminals are nickel plated copper alloy (gold plated optional, contact us for details)
- Each housing requires a wedge lock (must be ordered separately)
- Designed specifically for cable to cable applications on the engine or transmission, under the hood, on the chassis or in the cab.

Plug Connectors



Part Number	No. of Cavities	Wedge Lock	Repl. Seal	Fig.
DT06-2S	2	W2S	SEAL 2	A
DT06-3S	3	W3S	SEAL 3	B
DT06-4S	4	W4S	SEAL 4	C
DT06-6S	6	W6S	SEAL 6	D
DT06-08SA	8	W8S	SEAL 8	E
DT06-12SA	12	W12S	SEAL 12	F

Plug connectors accept socket terminals & have orange secondary locks. (All parts sold separately)

Receptacle Connectors



Part Number	No. of Cavities	Wedge Lock	Fig.
DT04-2P	2	W2P	A
DT04-3P	3	W3P	B
DT04-4P	4	W4P	C
DT04-6P	6	W6P	D
DT04-08PA	8	W8P	E
DT04-12PA	12	W12P	F

Receptacle connectors accept pin terminals & have green secondary locks. (All parts sold separately)

Solid Socket Terminals



Part Number	Contact Size	Wire Gauge
0462-201-16141	16	18-16
0462-209-16141	16	16-14*

*14ga. terminals supplied w/ painted green stripe to indicate 14ga.

Solid Pin Terminals



Part Number	Contact Size	Wire Gauge
0460-202-16141	16	18-16
0460-215-16141	16	16-14*

Open Barrel Socket Terminals



Part Number	Contact Size	Wire Gauge
1062-16-0122	16	18-16
1062-14-0122	16	16-14

Open Barrel Pin Terminals



Part Number	Contact Size	Wire Gauge
1060-16-0122	16	18-16
1060-14-0122	16	16-14

DT Series connectors will only accept contact size 16 terminals & plugs.

Sealing Plugs



Part Number	Contact Size
114017	16-12